

BOX FILLING STATION

MEC-31

Combining our know-how and experience we developed an innovative box filling station to pack "baguette" style products (white or artisan). The machine runs at high speed and guarantees a perfect organisation of the products into boxes.





Easy to use, to clean & to maintain

- Open frame with wide access doors.
- Easy cleaning with tool-free removable section doors.
- Automatic release of top hoppers at operator level for **safe and easy access**.

High efficiency & perfect filling

- From 2500 up to 9000 baguettes.
- Gentle product handling.
- **Trouble free** case packing even with poor quality boxes.



TECHNICAL SPECIFICATIONS MEC-31

2 versions (see capacities)

- Version -S (standard configuration)
- Version -L (artisan style)

Hygienic design

- Open frame design.
- Removable doors for easy hopper & door cleaning.

Quick & easy tool free belt removal

- Endless belt.
- Guides stay in position when removing the belt.
- Roller supported belt for less noise, less friction, no black marks.

Automatic lateral box positioning

• Roller guides mounted on spring system for box width compensation (+/- 5 mm).

Recipe

Movable hopper side: automatic adjustment of the position by recipe.

Hopper drive

- Brushless motors with belt drive system and plug & play replacement program.
- Quick release belt for easy access, cleaning, easy maintenance.
- Detection of loose belt by torque control (easy jam detection).

Standard with

remote access point (one per line)

CAPACITIES			
Box rate	Up to 8 boxes / min Box Dimensions: to be confirmed depending on the product organisation		
	VERSION S	VERSION L	
Lengthwise	Up to 9.000 baguettes/hour	Up to 9.000 baguettes/hour	
Bulk	Up to 60.000 small products/hour	Up to 60.000 small products/hour	
OPTIONS			
Side by side	Up to 10.000 1/2-baguettes/hour	Up to 13.000 1/2 baguettes/hour	
Crosswise	Up to 10.000 1/2-baguettes/hour	Up to 13.000 1/2 baguettes/hour	
CONSUMPTION	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	
Installed power	2 kw	2 kw	
Voltage	3 x 400 V + N + E / 50 Hz	3 x 400 V + N + E / 50 Hz	
Air supply	6.2 bars	6.2 bars	
Air consumption	500-600 NI / min	500-600 NI / min	
Weight	1700 kg	1700 kg	
CONSTRUCTION			
Stainless steel cons	truction		
Transversal conveyo	or with endless belt		
Open frame			
OPTIONS (More optio	ns are available, please contact Pat	tyn Bakery Division)	
Automatic box posit	ioner		
Extended box length	n: over 650 mm and up to 750 mm		
Open boxes higher t	han 500 mm		
Rejection bin			
Products packed sig	de by side		
Products packed cre	osswise		




T +33 5 65 65 19 05 info@pattyn.com www.pattyn.com






Removable doors




Transversal conveyor belts with tool free removal




Automatic lateral box positioning



Box Filling Station MEC-31-L



MEC-31-S Machine height 2660 mm



MEC-31-L Machine height 2660 mm

The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customised executions please contact Pattyn. MEC-31 2021 - V01

