


CHECKWEIGHER CW-11

The CW-11 weighs the box and checks if the weight is situated between the set limits. Also available with reject conveyor.



EASY TO
INTEGRATE



Check your box weight

- Specially designed for bulk bag-in-box applications.
- Compact solution to check the weight of boxes.
- Perfect integration into complete Pattyn line, with HMI for easy operation and communication.

Maximize your productivity

- Standard checkweigher **up to 12 c/min.**
- Continuous checkweigher for speeds **above 12 c/min.**



Watch our videos
at [pattyn.com](https://www.pattyn.com)

TECHNICAL SPECIFICATIONS CW-11

Easy to use

- Weight is checked according to the set limits.
- Conveyor of the checkweigher stops when the weight is out of the set tolerance. The reject conveyor (optional) rejects the box when the weight is not between the min/max limits.
- Thanks to the use of a roll conveyor instead of a belt, the box will be rejected in the same position.
- To reach a higher speed, a continuous checkweigher is required.

Modular & hygienic design

- Easy to integrate in complete line.
- Standard stainless steel frame.
- Removable conveyor for easy cleaning.

Standard equipped with

- Colour touch panel for easy operation
- Remote access point (one per line)




User friendly colour touch panel




Conveyor with load cell and stop




Optional reject conveyor


CONTAINER SPECIFICATIONS (For other dimensions, please contact Pattyn)	
Type	Cases, trays, plastic crates
Range (L x W // D) inches	Min. 12" (L) x 8" (W) // 4" (D) Max. 31 1/2" (L) x 19 1/2" (W) // 25 1/2" (D)
	Outside dimensions
OUTPUT AND CONSUMPTION	
Output checkweigher	Up to 12 c/min
Output continuous checkweigher	For speeds above 12 c/min
Maximum load	66 lbs
Deviation	e = d = 10 g (e = calibration unit, d = reading unit)
Dynamic accuracy	+/- 20 g for max. 12 c/min
Installed power	1 kW
Voltage	3 x 480V + E / 60 Hz
Air supply	90 PSI, (1/2" min)
Air consumption	0.18 ft ³ / cycle
Weight	441 lbs
OPTIONS (More options are available, please contact Pattyn)	
Reject mechanism	




Checkweigher



Checkweigher with reject



Continuous Checkweigher



Continuous Checkweigher with reject

Machine height: 83,5 inches

Min. conveyor length = 26" but will be modified according to case length if case length > 26"

Pattyn North America Inc.
N76 W30500 County Road Vv
Hartland, WI. 53029 - U.S.A

Ph +1 262-966-0300
Fax +1 262-966-0312
SalesUsa@pattyn.com



The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customized executions please contact Pattyn. CW-11 2021 - V01



Turnkey solutions for industrial packaging.