

BOX FILLING STATION

MEC-31

Combining our know-how and experience we developed an innovative box filling station to pack "baguette" style products (white or artisan). The machine runs at high speed and guarantees a perfect organisation of the products into boxes.





Easy to use, to clean & to maintain

- Open frame with wide access doors.
- Easy cleaning with tool-free removable section doors.
- Automatic release of top hoppers at operator level for **safe and easy access**.

High efficiency & perfect filling

- From 2500 up to 9000 baguettes.
- Gentle product handling.
- **Trouble free** case packing even with poor quality boxes.



TECHNICAL SPECIFICATIONS MEC-31

2 versions (see capacities)

- Version -S (standard configuration)
- Version -L (artisan style)

Hygienic design

- Open frame design.
- Removable doors for easy hopper & door cleaning.

Quick & easy tool free belt removal

- Endless belt.
- Guides stay in position when removing the belt.
- Roller supported belt for less noise, less friction, no black marks.

Automatic lateral box positioning

• Roller guides mounted on spring system for box width compensation (+/- 5 mm).

Recipe

• Movable hopper side: automatic adjustment of the position by recipe.

Hopper drive

- Brushless motors with belt drive system and plug & play replacement program.
- Quick release belt for easy access, cleaning, easy maintenance.
- Detection of loose belt by torque control (easy jam detection).


Standard with

remote access point (one per line)


Box rate	Up to 8 boxes / min Box Dimensions: to be confirmed depending on the product organisation		
	VERSION S	VERSION L	
Lengthwise	Up to 9.000 baguettes/hour	Up to 9.000 baguettes/hour	
Bulk	Up to 60.000 small products/hour	Up to 60.000 small products/hour	
OPTIONS			
Side by side	Up to 10.000 1/2-baguettes/hour	Up to 13.000 1/2 baguettes/hour	
Crosswise	Up to 10.000 1/2-baguettes/hour	Up to 13.000 1/2 baguettes/hour	
CONSUMPTION	· · · · · · · · · · · · · · · · · · ·	i	
Installed power	2 kw	2 kw	
Voltage	3 x 480 V + E / 60 Hz	3 x 480 V + E / 60 Hz	
Air supply	6 bar / 90 PSI	6 bar / 90 PSI	
Air consumption	500-600 NI / min	500-600 NI / min	
Weight	3747 lbs	3747 lbs	
CONSTRUCTION			
Stainless steel constr	ruction		
Transversal conveyor	with endless belt Op	en frame	
OPTIONS (More option	s are available, please contact F	Pattyn Bakery Division)	
Automatic box positio	ner		
Extended box length:	over 25.5" and up to 29.5"		
Open boxes higher than 19.7"		jection bin	
Products packed side by side		oducts packed crosswise	



Removable doors




Transversal conveyor belts with tool free removal




Automatic lateral box positioning



Box Filling Station MEC-31-L



MEC-31-S Machine height 8'7"



MEC-31-L Machine height 8'7"

Pattvn

ZI de la Glèbe - 314 Rue de la murette 12200 SAVIGNAC - France T +33 5 65 65 19 05 info@pattyn.com www.pattyn.com



The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customised executions please contact Pattyn. MEC-31 2021 - V01

