

PATTYN®

HOT MELT



Why hot melt?

Case Erector: CE-31

Case Erector-Bag Inserter: CEFLEX-41

1. CE-31 & CEFLEX-41 with hot melt execution

CE-31:

Standard equipped with:

- Nordson hot melt device.
- Hot melt nearly finished: hot melt level detection enables refilling before hot melt is completely empty.
- 15" HMI.



Standard: up to 16 c/min.

Also available in tape execution:

- Standard with 15" HMI.
- Standard output: up to 12 c/min.

CEFLEX-41:

Standard equipped with:

- Nordson hot melt device.
- Hot melt nearly finished: hot melt level detection enables refilling before hot melt is completely empty.
- 15" HMI.








Standard: up to 12 c/min

Also available in tape execution:

- Standard with 15" HMI.
- Standard output: up to 12 c/min.

2. Pattyn recommends hot melt

	HOT MELT	TAPER
Continuity	Continuous production, even during refill	Production stop during tape exchange
Running cost	Cost hot melt glue/case < cost tape/case	Cost tape/case > cost hot melt glue/case
Speed	CE-31: standard up to 16 c/min CEFLEX-41: standard up to 12 c/min	CE-31: standard up to 12 c/min CEFLEX-41: standard up to 12 c/min
Stability	Flat bottom: • Stable on conveyor 	V-shaped bottom: • Instable on conveyor 
	• Stable on pallet 	• Instable on pallet 
Risk on contamination	No contamination	Contamination of tape on conveyors. 

3. A trouble-free hot melt use



- Use good quality hot melt glue, resistant to high temperatures. Follow the requirements on the efficiency sheet: EG_Hotmelt_EN.
- Downwards spraying of the nozzles eliminates the risk of clogging.
- Store hot melt glue in a closed container to preserve the quality of the glue and to eliminate contamination.
- Maintain the Nordson hot melt unit twice a year with the maintenance contract of Nordson. Nordson offers worldwide local support.

Pattyn North America Inc.
N56 W24660 N. Corporate Circle
Sussex, WI. 53089 - U.S.A

Ph +1 262-966-0300
Fax +1 262-966-0312
SalesUsa@pattyn.com

pattyn.com

The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customized executions please contact Pattyn. Hot melt 2020-V01

PATTYN[®]

Turnkey solutions for industrial packaging.