




## BAG INSERTER ZIM-32

From a roll of polyethylene film, the **high speed** ZIM-32 automatically inserts bags into boxes, crates or trays.


The bag inserter runs with **made-to-measure bags or pre-made bags from a 12 kg reel** at a high speed and can handle multiple box footprints.



made-to-measure  
bags from a reel



pre-made bags  
from a reel



### Case lining for high output

- Up to 30 cases / minute
- Continuous production thanks to the **automatic film roll exchange**.
- **Compact footprint**.

### Your intelligent bag inserter

- Quick and **ergonomic film roll loading**.
- **Patented smart film opening technology**.
- **15" HMI** to facilitate operator convenience.



Watch our videos  
at [pattyn.com](https://pattyn.com)

# TECHNICAL SPECIFICATIONS

## ZIM-32

### Made-to-measure bags from a reel

- Continuous tubular gusseted film on a reel.
- Impulse sealing for a controlled and clean seal.

### Pre-made bags from a reel

- Pre-sealed and perforated bags on a reel for optimal convenience.

### Failsafe bag opening

- New strong gripper and spoon module.
- Patented smart film opening technology with a special vacuum and air insertion system.

### Perfectly controlled bag insertion


- Case flap holders for perfect case flap positioning.
- Servo driven up and down movement of the gripper frame for a steady and smooth operation.
- Integrated bag position control

### Operator friendly design


- Good maintenance accessibility.
- Improved interface to facilitate operator convenience.

### Standard equipped with:


- 15" HMI.
- Remote Access Point (one per line).
- Infeed conveyor with separator.



Automatic film roll exchange





Case flap holders




Strong gripper and spoon



15" HMI

CONTAINER SPECIFICATIONS (For other dimensions, please contact Pattyn)	
Type	Boxes, trays and crates
Range (L x W // D) mm	<b>Multi footprint (L x W) /variable heights</b> Min. 12" x 8" // 10" Max. 24" x 16" // 26"
 	Outside dimensions
FILM SPECIFICATIONS	
Type	Tubular film with gussets
Thickness	From 0.6 mil
Weight of film roll	Max. 26lbs
Outside diameter film roll	Max. 9"
Inside diameter of core	3"
OUTPUT AND CONSUMPTION	
Output	Standard up to 30 c/min (Depending on case sizes)
Installed power	7 kW (or 9 kW with two line sealing)
Voltage	3 x 480 V + E / 60 Hz
Air supply	6 bar / 1/2" min
Air consumption	90 NI / cycle
Weight	3043 lbs
OPTIONS (More options are available, please contact Pattyn)	
Automatic format change	Advanced stainless steel execution
Thermo transfer printer	Air plunger for improved bag positioning
4 roll random execution	



Machine height with film roll door closed: 83"  
Machine height with film roll door open: 89"

Pattyn Belgium nv  
Industriepark 'Blauwe Toren'  
Hoge Hul 2, 8000 Brugge - Belgium

T +32 (0) 50 450 480  
info@pattyn.com  
www.pattyn.com



The description, pictures and information given have an indicative value. We reserve the right to make changes without notice. Information and content is property of Pattyn. For customised executions please contact Pattyn. ZIM-32 2024 - V01

**PATTYN®**

Turnkey solutions for industrial packaging.